Grade A LFP(lithium iron phosphate) cells to ensure safety and performance





LOW VOLTAGE SERIES



LFP (lithium iron phosphate) cell to ensure the highest safety



MMD-RM-16S100/200

General Information	Rated Voltage	51.2Vdc	
	Rated Capacity	100Ah	200Ah
	Rated Energy	5.12kWh	10.24kWh
	Output Voltage Range	44.8V-57.6V	
	Charging Voltage (MAX)	58.4V	
	Cut-Off Voltage	40V	
	IP Rating	IP 21	
	Recommended Charging Current	20A	40A
	Max. Discharging Current	100A	
	Efficiency (Round Trip)	≥98%	
Physical Information	Dimension L*W*H(mm)	480*442*155 3.5U	680*442*222 50
	Weight (Kg)	≈44.5	≈86
	Humidity	5%~95% Relative Humidity	
	Charging Temperature	0°C~55°C	
	Discharging Temperature	-20℃~55℃	
	Storage Temperature	-10°C~30°C	
	Cycle Life (0.2C, @25°C, 80%DoD)	≥6500 Times	
	Design Life	≥15 Years	
	Mounting Options	Rack or Stack Wall	

Product Details



- LFP (lithium iron phosphate) cell to ensure the highest safety
- Built-In BMS protects the cell such as Temperature, Current, Voltage, SoC
- SoH Extra long cycle life times with 6500 cycles with 80% DoD
- Compatible with most of the available Inverters
- Possibility of parallel connection with up to 16 pieces



www.mmd-solar.com



- 1)Optimal self-consumption during day&night.
- 2)Independence from solar radiation and public grid.
- **3)**Economic,cost-cutting and ecofriendly.
- 4) Lightweight, safe and space saving.
- **5)**Modular installation: the storage capacity can be adapted to your needs.